

## **00020S01 Hazard Communication Information**

The Owner, the Contractor, and Subcontractors will be under the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Contractor and Subcontractors must provide their own written Hazard Communication Program. The Hazard Communication Program must include:

- (1) A list of the hazardous chemicals to which the Contractor's or Subcontractor's employees may be exposed;
- (2) Statement of the measures that Contractor's employees and Subcontractors may take to lessen the possibility of exposure to the hazardous materials;
- (3) The location of and access to the MSDSs related to the hazardous chemicals located in the work area; and
- (4) Procedures that the Contractor's employees and Subcontractors are to follow if they are exposed to hazardous chemicals above the Permissible Exposure Limit (PEL).

Material Safety Data Sheets (MSDS) may be reviewed upon request by the Contractor or any subcontractor as they pertain to the work areas of the project. Photocopies of the MSDSs may be made by Contractor at its expense.

The Contractor and Subcontractors shall provide the Owner with a list of any hazardous materials that will be used on the job site to which the Owner's employees may be exposed. The Contractor and Subcontractors shall provide the Owner with copies of Material Data Sheets for such materials to be used.

**NOTWITHSTANDING ANY INFORMATION PROVIDED IN THIS DOCUMENT,  
CONTRACTOR SHALL PERFORM WORK IN ACCORDANCE WITH ALL  
APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS AND ACCEPTED  
SAFETY PRACTICES.**