## 230548S01 Vibration and Seismic Controls for HVAC

TYPE OF SPACE	MAXIMUM ACCEPTABLE NOISE CRITERIA (NC) CURVE
GENERAL CLASSROOMS/LIBRARIES RESIDENCE-MULTIPLE OCCUPANT BANQUET HALL/BALLROOMS MUSEUM/DISPLAY AREA LABORATORIES RESTAURANT RECREATION HALLS LOBBIES/HALLS/CORRIDORS CAFETERIA RETAIL SPACE KITCHEN/LAUNDRY/GARAGE RESTROOMS/LOCKER ROOMS	35 35 35 40 40 40 40 40 40 45 45 45 45
MEDICAL FACILITY PATIENT ROOMS OPERATING ROOMS/WARDS WAITING ROOMS	25 35 40
OFFICES BOARD ROOMS CONFERENCE ROOMS PRIVATE OFFICE/RECEPTION ROOMS OPEN OFFICE/STUDIO TABULATION/COMPUTATION	25 30 35 40 45
AUDITORIUMS CONCERT HALLS/SOUND STUDIO LEGITIMATE THEATER MOVIE THEATER/LECTURE HALL	15 25 32
SPORTS CENTER COLISEUM GYMNASIUM SWIMMING POOL	35 40 50